



TECHNICAL DATA | E-THERM

SPECIFICATIONS

Propane consumption: 36-48 kg/ha **Working speed:** 4-6 km/h
Hydraulics: 22,5 l/m (depending on weed density)

Width Options: customizable from 1,5 m and up, with foldable designs for transport.

Front or rear mounting using the tractor's three-point hitch system



| | E-THERM 1500-3200 | | E-THERM 3500-6600 | |
|---------------------------|---|----------------|--|------------------|
| Capacity: | 2.23 - 3.16 acres per hour at 3.7 MPH (9.000 - 12.800 m ² per hour at 6 km/h) | | 3.46 - 9.80 acres per hour at 3.7 MPH (14.000-39.600 m ² per hour at 6 km/h) | |
| Power: | 1.770 - 3.540 btu | 519-1.037 kW | 3.865 - 7.403 btu | 1.133 - 2.171 kW |
| Weight: | 1.543 - 2.425 lb | 700 - 1.100 kg | 2.425 - 5.512 lb | 1.100 - 2.500 kg |
| Operational width: | 1,5 - 3,2 metres 60 - 126 in | | 3,5 - 6,6 metres 138 - 260 in | |

Configuration

Designed to fit your vegetable cultivation system

| Cultivation system | Porpane-Gas tank | Wheels | |
|--------------------|------------------|---------|----------|
| BEDS | CYLINDER | Ø 16 in | Ø 400 mm |
| RIDGES | BOTTLE | | |
| FLAT SOIL | TANK | Ø 24 in | Ø 600 mm |

Additional features

- Emergency stops system
- Easy to operate and maintain
- Online support for assistance
- Hydraulic lock

Benefits

- Low-noise
- Energy saving > 40%
- Wind tolerance
- CO₂ emissions reduction

**Have specific needs?
 Let us customise your solution**