



## TECHNICAL DATA | E-THERM



### SPECIFICATIONS

**Propane consumption:** 7-10 gpa.      **Working speed:** 3-4 mph  
**Hydraulics:** ± 6 gpm.                      (depending on weed density)

**Width Options:** customizable from 5 feet and up, with foldable designs for transport.



**Front or rear mounting using the tractor's three-point hitch system**



			E-THERM 1500-3200	E-THERM 3500-6600
<b>Capacity:</b>			2.23 - 3.16 acres per hour at 3.7 MPH (9.000 - 12.800 m <sup>2</sup> per hour at 6 km/h)	3.46 - 9.80 acres per hour at 3.7 MPH (14.000-39.600 m <sup>2</sup> per hour at 6 km/h)
<b>Power:</b>			1.770 - 3.540 btu      519-1.037 kW	3.865 - 7.403 btu      1.133 - 2.171 kW
<b>Weight:</b>			1.543 - 2.425 lb      700 - 1.100 kg	2.425 - 5.512 lb      1.100 - 2.500 kg
<b>Operational width:</b>			1,5 - 3,2 metres <b>60 - 126 in</b>	3,5 - 6,6 metres <b>138 - 260 in</b>

### Configuration

Designed to fit the specific cultivation system

Cultivation system	Propane Gas Container		Wheels	
BEDS	CYLINDER	Ø 16 in	Ø 400 mm	
RIDGES	BOTTLE			
FLAT SOIL	TANK	Ø 24 in	Ø 600 mm	

### Additional features

- Emergency stops system
- Easy to operate and maintain
- Online support for assistance
- Hydraulic lock

### Benefits

- Low-noise
- Energy saving > 40%
- Wind tolerance
- Reduction in CO<sub>2</sub> emissions

**Have specific needs?  
 Let us customize your solution**